


JCH ball valve Type 745517D with drain
Prevents frost damage.
With female threads. Reduced bore.
Prepared for AVK extension spindles and street covers.



Version 02_11



Reduced bore ball valve with femal threads:

Applications:

Service valve for water supply and sewage.

Test:

JCH 100% test

Accessories:

AVK extension spindles fixed lenght series 04/05.

AVK extension spindles telescopic series 04/07.

AVK street covers.


Material

Body:	DZR Brass CW602N
Pipecoupling:	DZR Brass CW602N
Spindle:	Stainless steel - AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	stainless acid proof steel - AISI 316
Top gasket:	NBR o-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH ball valve Type 745517D

with 12mm # operation key.

Prepared for AVK extension spindles and street covers.



Version 01_11

Service valve for water supply and sewage.



Order no.	LNS no.	RP "	DN mm	L mm	H mm	NV1 mm spindle	NV2 mm Valve	weight kg
745517-110D	343-025-54-10	1¼"	25	97	104	12	42	1,45
745517-111D	343-032-54-10	1½"	32	107	109	12	56	1,75
745517-112D	343-040-54-10	2"	40	117	119	12	70	2,65

J.C.HANSENS METALVAREFABRIK ApS

Karetmagervej 21 | DK-7100 Vejle | Tel. +45 75 85 84 08 | Fax +45 75 85 80 82
jchansen@jchansen.dk | www.jchansen.dk