


JCH Ballvalve Type 745517 With internal threads, reduced bore. VA and SITAC approved. Prepared for AVK ekstension spindles and streetcovers.



Version 01_11



JCH Ballvalve with internal threads:

Application: Stopvalve for watersupply, applicable for drilling under pressure.

Test: JCH 100% test

Accessories:

AVK extension spindles fixed length series 04/05.


AVK extension spindles telescopic series 04/07.

AVK streetcovers.

Material

Body:	DZR Brass CW602N
pipecoupling:	DZR Brass CW602N
Spindle:	Stainless steel -AISI 303
Spindle-gasket:	SEDI PTFE + O-rings of NBR rubber
Ball:	stainless acid proof steel -AISI 316
Top gasket:	NBR o-rings
Top union:	DZR Brass CW602N
Gasket inside:	SEDI PTFE

JCH Ballvalve Type 745517 with 12mm squarehead spindle.Prepared for AVK extension spindles and streetcovers.



Version 01_11

Ballvalve type 745517 is applicable as stopvalve in watersupplys the pipeconnections gives many diffrentopptunitiesit can be used for drilling, ballvalvetype 745517 is quikly and easily to install and use, made of the finest and best materials.



Order.	LNS Nr	RP "	DN mm	L mm	H mm	NV1 mm spindle	NV2 mm Valve	weight kg
745517-108	343-020-54-00	1"	20	82	99	12	39	1,04
745517-110	343-025-54-00	1¼"	25	97	104	12	42	1,45
745517-111	343-032-54-00	1½"	32	107	109	12	56	1,75
745517-112	343-040-54-00	2"	40	117	119	12	70	2,65

J.C.HANSENS METALVAREFABRIK ApS

Karetmagervej 21 | DK-7100 Vejle | Tel. +45 75 85 84 08 | Fax +45 75 85 80 82
 jchansen@jchansen.dk | www.jchansen.dk